MEMBRANE SEPARATION APPARATUS

Publication number: JP10033955 Publication date: 1998-02-10

Inventor: MATSUM OTO TOMOKI; IWASAKI KOICHI
Applicant: HITACHI SHIPBUILDING ENG CO

Classification:

B01D63/08; B01D65/02; C02F1/44; B01D63/08;

B01D65/00; C02F1/44; (IPC1-7): B01D63/08;

B01D65/02; C02F1/44

- European:


Application number: JP19960193127 19960723 Priority number(s): JP19960193127 19960723

Report a data error here

Abstract of JP10033955

PROBLEM TO BE SOLVED: To prevent the clogging of the air diffusion port of an air diffusion pipe end to disperse eir bubbles blown out of the air diffusion port throughout a liquid. SOLUTION: A membrane separation apparatus is equipped with a mambrane separation tank 1, a filter membrane unit 3 consisting of a lerge number of vartical hollow yam flet mambrane modules 2 arranged mutually perallel so as to leave intervals between them end arranged in the membrane separation tank 1 and a plurality of air diffusion pipes 4 arranged under the filter membrane units 2 in the membrana separation tank 1. The air diffusion pipes 4 are arranged mutually parallel so es to provide intervals therebatween. A plurality of lateral eir diffusion ports era formed to both sida parts of the pipe wall of each of the air diffusion pipes 4 so as to provide intervals in the length direction of the eir diffusion pipa. The air diffusion ports 6 of

the edjacent pipes 4 are mutually opposed.



Data supplied from the esp@cenet database - Worldwide